

# **GÖTEBORG®**

## Timeless elegance

The GÖTEBORG concrete roof tile is timeless and universal thanks to its shape referring to the classic S-shaped roof tile. It works perfectly on the roof of a building with a traditional shape. This is an ideal proposition for lovers of always fashionable elegance. GÖTEBORG, thanks to numerous construction solutions, is characterized by high durability and resistance.

Dimensions: 334 x 420 mm Consumption: from 9.7 pcs/m2

Weight: 4.6 kg/pcs.





#### Timeless shape

Reference to the classic S-shaped roof, perfect for any roof



#### Proper profiling

Overlaps and smooth edges protect against moss and sediment



#### **Understructure**

Increased resistance to wind and snow loads



#### Modern surfaces

Protection against water and dirt ingress



#### Rich colors

Durable colors resistant to UV and weather conditions



# Comprehensive range of accessories

Aesthetic and durable roof finish



# Technical data for GÖTEBORG®

External dimensions	334 × 420 mm
Coverage width - min.	300 mm
Coverage width - av.	300 mm
Coverage width - max.	300 mm
Battens distance - min.	310 mm
Battens distance - av.	328 mm
Battens distance - max.	345 mm
Pcs/m² - min.	9,7 Pcs/m <sup>2</sup>
Pcs/m² - av.	10,2 Pcs/m <sup>2</sup>
Pcs/m² - max.	10,7 Pcs/m <sup>2</sup>
Kg/pc	4,6 Kg/pc
Kg/m²	47 Kg/m <sup>2</sup>
Mini pack - pcs	40 Pcs
Mini pack - weight	184 kg
Slope angle	≥ 10°

### **Colours**















#### CREATON Polska sp. z o.o.

ul. Wspólna 6 32-300 Olkusz, Polska tel. +48 32 624 95 00 centrala@swisspor.pl

All technical changes are reserved. The company is not liable for printing errors or for deviations in color shades, caused by the use of specific printing techniques. The product photos shown in the catalog are for illustrative purposes and may differ from the actual appearance of the products on sale.